



SAFETY DATA SHEET AMSOIL Glass Cleaner

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

1. Identification	
Product identifier	
Product name	AMSOIL Glass Cleaner
Product number	AGCSC
Recommended use of the che	emical and restrictions on use
Application	Glass cleaner.
Uses advised against	No specific uses advised against are identified.
Details of the supplier of the s	afety data sheet
Supplier	AMSOIL INC. Bordner, Ladner, Gervais Scotia Plaza, 40 King St W Toronto, ON, Canada M5H 3Y4 T: +1 416-367-6547
Manufacturer	AMSOIL INC. One AMSOIL Center, Superior, WI 54880, USA. T: +1 715-392-7101 compliance@amsoil.com
Emergency telephone number	<u>r</u>
Emergency telephone	CHEMTREC: Within USA and Canada: 1-800-424-9300 Outside the USA and Canada: +1 703-741-5970 (collect calls accepted) 24/7
2. Hazard(s) identification	
Classification of the substance	e or mixture
OSHA/WHMIS Regulatory Status	This Product is Hazardous under the OSHA Hazard Communication Standard and according to the hazard criteria of the Hazardous Product Regulations.
Physical hazards	Aerosol 3 Press. Gas, Compressed - H280
Health hazards	Not Classified
Environmental hazards	Not Classified
Label elements	
Pictogram	
$\langle \cdot \rangle$	
Signal word	Warning
Hazard statements	H280 Contains gas under pressure; may explode if heated.
	1/40

SAVE UP TO 25%

AMSOIL Glass Cleaner

Precautionary statementsP210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
P251 Pressurized container: Do not pierce or burn, even after use
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P412 Do not expose to temperatures exceeding 50°C/122°F.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients	
Mixtures	
Ethanol	3 - <5%
CAS number: 64-17-5	
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2A - H319	
2-Butoxyethanol	1 - <2.5%
CAS number: 111-76-2	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures	
Description of first aid meas	sures
General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin Contact	Rinse with water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.



AMSOIL Glass Cleaner

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. Most important symptoms and effects, both acute and delayed See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Inhalation Spray/mists may cause respiratory tract irritation. Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur. Skin contact Repeated exposure may cause skin dryness or cracking. Eye contact May be slightly irritating to eyes. May cause discomfort. Indication of immediate medical tention and special treatment needed Notes for the doctor Terrefighting measures Extinguishing media Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media Special hazards arising from t= substance or mixture Special hazards arising from tares can burst violently or explode when heated, due to excessive pressure build-up. Bursting aecrosi containers may be propelled from a fire at high speed. If aerosoi cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Avoid breathing fire gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water until		
General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Inhalation Spray/mists may cause respiratory tract irritation. Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur. Skin contact Repeated exposure may cause skin dryness or cracking. Eye contact May be slightly irritating to eyes. May cause discomfort. Indication of immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. 5. Fire-fighting measures Extinguishing media Suitable extinguishing media Suitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if i can be done without risk. Cool containers exposed to f	Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.
Inhalation Spray/mists may cause respiratory tract irritation. Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur. Skin contact Repeated exposure may cause skin dryness or cracking. Eye contact May be slightly irritating to eyes. May cause discomfort. Indication of immediate medical attention and special treatment needed Treat symptomatically. 5. Fire-fighting measures Extinguishing media Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are rupured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray to disperse vapors and protect men stopping the leak. Contorl run-off water by containing and keeping it to ut of swers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective cloting. Standard Firefighter's clothing including helments, protective boots and glocus, notify appropriate authoritis.	Most important symptoms and	effects, both acute and delayed
IngestionDue to the physical nature of this product, it is unlikely that ingestion will occur.Skin contactRepeated exposure may cause skin dryness or cracking.Eye contactMay be slightly irritating to eyes. May cause discomfort.Indication of immediate medical attention and special treatment neededNotes for the doctorTreat symptomatically.5. Fire-fighting measuresExtinguishing mediaSuitable extinguishing mediaSuitable extinguishing mediaSuitable extinguishingDo not use water jet as an extinguisher, as this will spread the fire.Special hazards arising from the substance or mbxtureSpecific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant.Hazardous combustion produdsThermal decomposition or combustion products may include the following substances: Harmful gases or vapors.Advice for firefighters Protective actions during firefightingAvoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to filmes with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of severs and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-press	General information	
Skin contact Repeated exposure may cause skin dryness or cracking. Eye contact May be slightly irritating to eyes. May cause discomfort. Indication of immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. 5. Fire-fighting measures Extinguishing media Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire- extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Special hazards arising from the substance or mixture Sursting aerosol containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of severs and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apa	Inhalation	Spray/mists may cause respiratory tract irritation.
Eye contact May be slightly irritating to eyes. May cause discomfort. Indication of immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. 5. Fire-fighting measures Extinguishing media Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Special hazards arising from the substance or mkture Special hazards Special hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion Thermaf decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray to disperse vapors and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including hemets, protective boots and gloves, that provides a basic level of protecton during chemical incidents is defined by t	Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Indication of immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. 5. Fire-fighting measures Extinguishing media Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Special hazards arising from the substance or mixture Special hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flaames with water until well after the fire is out. If a leak or spill has not ignited, use water spiray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing in	Skin contact	Repeated exposure may cause skin dryness or cracking.
Notes for the doctor Treat symptomatically. 5. Fire-fighting measures Extinguishing media Suitable extinguishing media Extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Special hazards arising from the substance or mixture Specific hazards Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect me stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. S	Eye contact	May be slightly irritating to eyes. May cause discomfort.
5. Fire-fighting measures Extinguishing media Suitable extinguishing media Extinguishing media Extinguishing media Extinguishing media Extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Special hazards arising from the substance or mixture Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective cothing. Standard Firefighter's clothing including helmets, protective bots and gloves, that provides a basic level of protection during chemical	Indication of immediate medic	al attention and special treatment needed
Extinguishing media Suitable extinguishing media Extinguishing media Extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Special hazards arising from the substance or mixture Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Notes for the doctor	Treat symptomatically.
Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Special hazards arising from the substance or mixture Specific hazards Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including heimets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on o	5. Fire-fighting measures	
extinguishing media suitable for the surrounding fire.Unsuitable extinguishing mediaDo not use water jet as an extinguisher, as this will spread the fire.Special hazards arising from the substance or mixtureSpecific hazardsSpecific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant.Hazardous combustion productsThermal decomposition or combustion products may include the following substances: Harmful gases or vapors.Advice for firefightersAvoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Extinguishing media	
media Special hazards arising from the substance or mixture Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect me stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Suitable extinguishing media	
Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Advice for firefighters Protective actions during firefighting Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.		Do not use water jet as an extinguisher, as this will spread the fire.
Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant.Hazardous combustion productsThermal decomposition or combustion products may include the following substances: 	Special hazards arising from the	he substance or mixture
productsHarmful gases or vapors.Advice for firefightersProtective actions during firefightingAvoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Specific hazards	Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and
Protective actions during firefightingAvoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.		
firefightingwater spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Advice for firefighters	
for firefighters clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	-	water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs,
6. Accidental release measures		clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health
	6. Accidental release measure	95

Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Do not touch or walk into spilled material.

Environmental precautions

SAVE UP TO 25%

AMSOIL Glass Cleaner

Environmental precautions Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Approach the spillage from upwind. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
7. Handling and storage	
Precautions for safe handling	
Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapors and spray/mists.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.
Conditions for safe storage, in	cluding any incompatibilities
Storage precautions	Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.
Storage class	Chemical storage.
Specific end uses(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.
8. Exposure Controls/personal	protection
Control parameters	

Occupational exposure limits



AMSOIL Glass Cleaner

Comments

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Ethanol

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 1900 mg/m³ Short-term exposure limit (15-minute): ACGIH 1000 ppm 1880 mg/m³ A3

2-Butoxyethanol

Long-term exposure limit (8-hour TWA): OSHA 50 ppm 240 mg/m³ Sk

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 97 mg/m³ A3

OSHA = Occupational Safety and Health Administration. ACGIH = American Conference of Governmental Industrial Hygienists.

Sk = Danger of cutaneous absorption.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

Ethanol (CAS: 64-17-5)

Immediate danger to life	3300 ppm
and health	

2-Butoxyethanol (CAS: 111-76-2)

Immediate danger to life	700 ppm
and health	

Exposure controls

Appropriate engineering controls	Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

SAVE UP TO 25%

AMSOIL Glass Cleaner

Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.
Environmental exposure controls	Keep container tightly sealed when not in use.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

	<u> </u>
Appearance	Aerosol.
Color	White foam.
Odor	Pleasant, agreeable.
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not available.
Evaporation rate	Slower than ether.
Upper/lower flammability or explosive limits	Not available.
Other flammability	Level: 1 Aerosol.
Vapor pressure	Not available.
Vapor density	> Air
Relative density	Not available.
Solubility(ies)	Not known.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not considered to be e
Oxidizing properties	Does not meet the crit
Other information	No information require



AMSOIL Glass Cleaner

10. Stability and reactivity	
Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
11. Toxicological information	
Information on toxicological eff	iects
Acute toxicity - oral	
Notes (oral LD₅o)	Based on available data the classification criteria are not met.
ATE oral (mg/kg)	87,300.0
Acute toxicity - dermal	
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	55,000.0
Acute toxicity - inhalation	
Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
ATE inhalation (vapours mg/l)	550.0
Skin corrosion/irritation Animal data	Based on available data the classification criteria are not met.
Serious eye damage/irritation Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitization Respiratory sensitization	Based on available data the classification criteria are not met.
Skin sensitization Skin sensitization	Based on available data the classification criteria are not met.
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	Contains a substance/a group of substances which may cause cancer. IARC Group 1 Carcinogenic to humans.
Reproductive toxicity	



SAVE UP TO 25%

AMSOIL Glass Cleaner

Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicity -	single exposure
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Specific target organ toxicity -	repeated exposure
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Spray/mists may cause respiratory tract irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin Contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May be slightly irritating to eyes. May cause discomfort.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
12. Ecological Information	
12. Ecological Information Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
Ecotoxicity	hazardous effects on the environment.
Ecotoxicity Toxicity Persistence and degradability	hazardous effects on the environment.
Ecotoxicity Toxicity Persistence and degradability	hazardous effects on the environment. Based on available data the classification criteria are not met.
Ecotoxicity Toxicity Persistence and degradability Persistence and degradability	hazardous effects on the environment. Based on available data the classification criteria are not met.
Ecotoxicity Toxicity Persistence and degradability Persistence and degradability Bioaccumulative potential	hazardous effects on the environment. Based on available data the classification criteria are not met. The degradability of the product is not known.
Ecotoxicity Toxicity Persistence and degradability Persistence and degradability Bioaccumulative potential Bio-Accumulative Potential	hazardous effects on the environment. Based on available data the classification criteria are not met. The degradability of the product is not known. No data available on bioaccumulation.
Ecotoxicity Toxicity Persistence and degradability Persistence and degradability <u>Bioaccumulative potential</u> Bio-Accumulative Potential Partition coefficient	hazardous effects on the environment. Based on available data the classification criteria are not met. The degradability of the product is not known. No data available on bioaccumulation.
Ecotoxicity Toxicity Persistence and degradability Persistence and degradability Bioaccumulative potential Bio-Accumulative Potential Partition coefficient Mobility in soil	 hazardous effects on the environment. Based on available data the classification criteria are not met. The degradability of the product is not known. No data available on bioaccumulation. Not available. The product contains volatile organic compounds (VOCs) which will evaporate easily from all
Ecotoxicity Toxicity Persistence and degradability Persistence and degradability Bioaccumulative potential Bio-Accumulative Potential Partition coefficient <u>Mobility in soil</u> Mobility	 hazardous effects on the environment. Based on available data the classification criteria are not met. The degradability of the product is not known. No data available on bioaccumulation. Not available. The product contains volatile organic compounds (VOCs) which will evaporate easily from all
Ecotoxicity Toxicity Persistence and degradability Persistence and degradability Bioaccumulative potential Bio-Accumulative Potential Partition coefficient Mobility in soil Mobility Other adverse effects	 hazardous effects on the environment. Based on available data the classification criteria are not met. The degradability of the product is not known. No data available on bioaccumulation. Not available. The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

SAVE UP TO 25%

AMSOIL Glass Cleaner

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

UN Number	
UN No. (TDG)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (DOT)	1950
	1000
UN proper shipping name	
Proper shipping name (TDG)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (DOT)	AEROSOLS
Transport hazard class(es)	
DOT hazard class	2.2
DOT hazard label	2.2
TDG class	2.2
TDG label(s)	2.2
IMDG Class	2.2

ICAO class/division

14. Transport information

DOT transport labels



Transport labels



Packing group TDG Packing Group

None

2.2

9/12



AMSOIL Glass Cleaner

IMDG packing group	None	
ICAO packing group	None	
DOT packing group	None	
Environmental hazards		
Environmentally Hazardous Su No.	ubstance	
Special precautions for user		
EmS	F-D, S-U	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.	
15. Regulatory information		
Regulatory References	OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation (SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.	
US Federal Regulations SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities None of the ingredients are listed or exempt. CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA) None of the ingredients are listed or exempt. SARA Extremely Hazardous Substances EPCRA Reportable Quantities None of the ingredients are listed or exempt. SARA 313 Emission Reporting The following ingredients are listed or exempt: 2-Butoxyethanol 1.0 % CAA Accidental Release Prevention None of the ingredients are listed or exempt.		
FDA - Essential Chemical None of the ingredients are listed or exempt.		
FDA - Precursor Chemical None of the ingredients are listed or exempt.		
SARA (311/312) Hazard Categories None of the ingredients are listed or exempt.		
OSHA Highly Hazardous Chemicals None of the ingredients are listed or exempt.		
US State Regulations California Proposition 65 Carcinogens and Reproductive Toxins None of the ingredients are listed or exempt.		

BUY ONLINE

FREE CATALOG



AMSOIL Glass Cleaner

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

2-Butoxyethanol

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

2-Butoxyethanol

Ethanol

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

2-Butoxyethanol

Ethanol

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

2-Butoxyethanol

Ethanol

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

2-Butoxyethanol

Ethanol

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

2-Butoxyethanol

Ethanol

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

2-Butoxyethanol

Ethanol

Inventories

Canada - DSL/NDSL All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

SAVE UP TO 25%

AMSOIL Glass Cleaner

Abbreviations and acronyms used in the safety data sheet	C.A.S. = Chemical Abstracts Service; E.C. No = European Commission number; GHS = Globally Harmonised System; OSHA = Occupational Safety and Health Administration; WHMIS = Workplace Hazardous Materials Information System; DOT = Department of Transport; TDG = Transport of Dangerous Goods Regulations; IMDG = International Maritime Dangerous Goods; IATA = International Air Transport Association; SARA = Superfund Amendments and Reauthorization Act; CERCLA = Comprehensive Environmental; EPCRA = Emergency Planning and Community Right-to-Know Act; TSCA = Toxic Substances Control Act; LD/LC/EC = Lethal Dose,Lethal Concentration/Effect Concentration for 50% of population; NOEC = No Overall Effect Concentration; NOEL = No Overall Effect Level; REACH = Registration, Evaluation, Authorisation & Restriction of Chemicals; STOT-RE = Single Target Organ Toxicity - Repeat Exposure; STOT-SE= Specific Target Organ Toxicity - Single Exposure; PBT = Persistent, Bioaccumulative, Toxic; vPvB = Very Persistent, Very Bioaccumulative.
Classification abbreviations and acronyms	Aerosol = Aerosol
Key literature references and sources for data	Source: European Chemicals Agency, http://echa.europa.eu/
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision date	4/4/2018
SDS No.	7354
Hazard statements in full	 H225 Highly flammable liquid and vapor. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.